

3000/3600 RPM

3 Phase AC (IE3)

220/460 Volts
50/60 Hertz
Star/Delta Connection
IC 411/TEFC Cooling
Class F Insulation
IP 55/IP44 Protection



Power		Frame	Mount	Full Load		Nominal Efficiency (%)	Product Code
(kW)	(Hp)			Speed (RPM)	Current (A)		
0.37	0.5	71	Foot	2810/3372	1.55/0.9	73.8	
			Flange				
			Foot + Flange				
0.55	0.75	71	Foot	2810/3372	2.42/1.4	77.8	
			Flange				
			Foot + Flange				
0.75	1.0	80	Foot	2800/3360	3.1/1.8	80.7	
			Flange				
			Foot + Flange				
1.1	1.5	80	Foot	2810/3372	4.3/2.4	82.7	
			Flange				
			Foot + Flange				
1.5	2.0	90	Foot	2825/3390	5.5/3.2	84.2	
			Flange				
			Foot + Flange				
1.8	2.5	100	Foot	2820/3384	6.3/3.6	85.0	
			Flange				
			Foot + Flange				
2.2	3.0	90	Foot	2825/3390	8.3/4.8	85.9	
			Flange				
			Foot + Flange				
2.2	3.0	100L	Foot	2840/3408	8.3/4.5	85.9	
			Flange				
			Foot + Flange				
3.7	5.0	100L	Foot	2870/3444	12.4/7.2	87.8	
			Flange				
			Foot + Flange				
3.7	5.0	112M	Foot	2870/3444	12.4/7.2	87.8	
			Flange				
			Foot + Flange				
5.5	7.5	132S	Foot	2890/3468	10.5/18.8	89.2	
			Flange				
			Foot + Flange				
7.5	10	132S	Foot	2890/3468	22.5/13.0	90.1	
			Flange				
			Foot + Flange				
11.0	15.0	160M	Foot	2910/3492	34.6/20.0	91.2	
			Flange				
			Foot + Flange				