

1500/1800 RPM

3 Phase AC (IE3)

220/460 Volts
50/60 Hertz
Star/Delta Connection
IC 411/TEFC Cooling
Class F Insulation
IP 55/IP44 Protection



Power		Frame	Mount	Full Load		Nominal Efficiency (%)	Product Code
(kW)	(Hp)			Speed (RPM)	Current (A)		
0.37	0.5	71	Foot	1410/1692	1.38/1.4	77.3	
			Flange				
			Foot + Flange				
0.55	0.75	80	Foot	1410/1692	2.9/1.7	80.8	
			Flange				
			Foot + Flange				
0.75	1.0	80	Foot	1425/1710	2.7/1.7	82.5	
			Flange				
			Foot + Flange				
1.1	1.5	90	Foot	1435/1722	3.8/2.3	84.1	
			Flange				
			Foot + Flange				
2.2	3.0	100L	Foot	1435/1722	7.7/4.5	86.7	
			Flange				
			Foot + Flange				
3.7	5.0	112	Foot	1435/1722	13.1/7.8	88.4	
			Flange				
			Foot + Flange				
5.5	7.5	132	Foot	1464/1756	18.7/10.8	89.6	
			Flange				
			Foot + Flange				
7.5	10	132	Foot	1464/1756	25.6/14.8	90.4	
			Flange				
			Foot + Flange				
11.0	15.0	160	Foot	1464/1756	36.0/21.0	91.4	
			Flange				
			Foot + Flange				
15.0	20.0	160	Foot	1464/1756	48.0/29.0	92.1	
			Flange				
			Foot + Flange				
18.5	25.0	180	Foot	1464/1756	35.0/60.6	92.6	
			Flange				
			Foot + Flange				
22	30.0	180	Foot	1464/1756	72.0/42.5	93.0	
			Flange				
			Foot + Flange				