

1000/1200 RPM

3 Phase AC (IE3)

220/460 Volts
50/60 Hertz
Star/Delta Connection
IC 411/TEFC Cooling
Class F Insulation
IP 55/IP44 Protection



Power		Frame	Mount	Full Load		Nominal Efficiency (%)	Product Code
(kW)	(Hp)			Speed (RPM)	Current (A)		
0.37	0.5	80	Foot	870/1044	2.4/1.4	73.5	
			Flange				
			Foot + Flange				
0.55	0.75	80	Foot	870/1044	3.3/1.9	77.2	
			Flange				
			Foot + Flange				
0.75	1.0	90	Foot	890/1068	3.9/2.3	78.9	
			Flange				
			Foot + Flange				
1.1	1.5	90	Foot	900/1080	5.8/3.4	81.0	
			Flange				
			Foot + Flange				
1.5	2.0	100L	Foot	900/1080	6.5/3.8	82.5	
			Flange				
			Foot + Flange				
2.2	3.0	112M	Foot	910/1092	9.5/5.5	84.3	
			Flange				
			Foot + Flange				
3.7	5.0	132S	Foot	920/1104	14.72/8.5	86.5	
			Flange				
			Foot + Flange				
5.5	7.5	132	Foot	920/1140	21.6/12.5	88.0	
			Flange				
			Foot + Flange				
7.5	10	160	Foot	930/1116	27.7/16.0	89.1	
			Flange				
			Foot + Flange				